

NEW



# Disinfect large areas quickly and safely

Mobile disinfection sprayers  
Made in Germany

**NEW**

available from 1 May 2020



# Mobile Disinfection Sprayers

Suitable for commercial disinfection solutions with a flashpoint higher than 55° C

- ✓ constant spray pressure for even, low-mist spray results
- ✓ adjustable flow volume
- ✓ saves time and money
- ✓ protects the environment and health

## Canister Pump Set 230 V ref. 7898



**Pump can be screwed directly onto the DIN 61 thread of a canister/jerry can**

Spray lance with flat fan nozzle no. 4, spraying angle 110°, approx. 950 ml per minute flow rate, and flat fan nozzle no. 2, spraying angle 110° approx. 690 ml per minute flow rate

set consists of:

- 230 V canister pump
- spray lance with flat fan nozzle
- 5 m reinforced hose
- PE canister 20 L

**Dimensions:**  
LxWxH 29 x 25 x 57 cm

### Accessories:

Adaptor set for canister pump ref. 11362  
Adapters to 2 inch thread, DIN 51 and DIN 71 threads, with longer suction hose and foot filter



- for large areas in public facilities, schools and buildings
- for machinery and work surfaces in industrial areas between shift changes
- for safety-sensitive areas in health services such as medical practices, hospitals etc.

For more information: [export@ceмо.de](mailto:export@ceмо.de)

Additions to our range of disinfection products are being developed!  
Subject to technical changes. © CEMO 04.20

## Container sprayer 230 V ref. 11356



Spray lance with flat fan nozzle no. 4, spraying angle 110°, approx. 1040 - 1370 ml per minute flow rate, and flat fan nozzle no. 2, spraying angle 110° approx. 800 - 1000 ml per minute flow rate

- container volume 20 L
- 230 V power
- 5 m cable length
- pressure control valve 0.3 - 5 bar
- 5 m reinforced hose
- spray lance with flat fan nozzle

**Dimensions:**  
LxWxH 56 x 21 x 38 cm

## Spray Caddy 60 L, 12 V ref. 11359



### Battery-operated

Battery capacity 3.3 Ah, sufficient for approximately 60 L (with nozzle 03)

Spray lance with flat fan nozzle no. 3, spraying angle 110°, approx. 1150 ml per minute flow rate, and flat fan nozzle no. 2, spraying angle 110° approx. 800 ml per minute flow rate

- 12 V pump with 100% duty cycle
- LiFePO4 battery with charger
- 8 m reinforced hose
- spray lance with flat fan nozzle

**Dimensions:**  
LxWxH 90 x 52 x 37 cm

### Accessories:

Spare battery ref. 10602  
12, 8 V 3.3 Ah Lithium Iron Phosphate battery

